

Sanitary & Storm Sewer Fittings

DR26 and DR35 sewer fittings allow for a tight, leak free connection.

Sewer fittings are manufactured using PVC sewer pipe by thermoforming sections of pipe and solvent welding together. Fittings are available in 100mm to 1500mm (4" to 60") diameters. A complete line of sewer fittings are available, including tees, wyes, bends, sweeps, couplings, caps, increasers, saddles and cleanouts.

- Water tight joints mean virtually no risk of infiltration or leakage
- Corrosion and abrasion-resistant
- Smooth interior walls allow for higher flow rates
- Easy to handle and install
- Also available in Nitrile Gaskets for extra chemical resistance

Galaxy Plastics sewer fittings bearing the CSA mark have been third party certified to CSA B182.2

Available from 100mm to 1500mm (4" to 60")



Sanitary & Storm Sewer Fittings

Fabricated Sewer fittings sizes 100mm, 135mm & 150mm (4", 5", 6") are manufactured from DR28 pipe. Sizes 200mm to 1500mm (8" to 60") can be manufactured from either DR35 or DR26 pipe.

Fabricated Fittings are manufactured using segments of PVC sewer pipe by pulling, bending, hubbing and solvent welding branches.

Galaxy Plastics Ltd Gasketed Sewer fittings use a Reiber gasket. The steel reinforced Reiber gasket is locked in the socket bell to resist the effect known as "fish mouthing".

Sewer fittings bearing the CSA mark have been Third Party certified to either CSA B182.2 or CSA B182.4. All gaskets meet the requirements of ASTM F477 and D3213.



