



LISTING INFORMATION OF
Galaxy Plastics - C900/C905 PVC Pressure Rated Pipe Fittings

SPEC ID: 17954

Galaxy Plastics Ltd.
#9-30321 Fraser Hwy.
Abbotsford, BC V4X 1T3
Canada

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

PRODUCT DESCRIPTION

C900/C905 PVC Pressure Fittings are intended for underground applications and are designed to be under pressure. These fittings come in a variety of types such as: 11° bend, 45° bend, Tee, increaser, coupling, cross, and cap. The product is available in two different design pressures DR18 and DR 25 which are rated at 235 PSI and 165 PSI respectively. The DR rating corresponds to the diameter to wall-thickness ratio. The pressure fittings come in a variety of diameters and corresponding wall thicknesses to maintain the diameter to wall-thickness ratio.

MODELS

Note: All dimensions given in inches.

TEES (Gasket x Gasket x Gasket)

C900 (DR18)

4 x 4 x 4

6 x 6 x 4, 6

8 x 8 x 4, 6, 8

10 x 10 x 4, 6, 8, 10

12 x 12 x 4, 6, 8, 10, 12

C905 (DR18)

14 x 14 x 4, 6, 8, 10, 12, 14

16 x 16 x 4, 6, 8, 10, 12, 14, 16

18 x 18 x 4, 6, 8, 10, 12, 14, 16, 18

20 x 20 x 4, 6, 8, 10, 12, 14, 16, 18, 20

24 x 24 x 4, 6, 8, 10, 12, 14, 16, 18, 20, 24

C905 (DR25)

30 x 30 x 4, 6, 8, 10, 12, 14, 16, 18, 20, 24, 30

36 x 36 x 4, 6, 8, 10, 12, 14, 16, 18, 20, 24, 30, 36

CROSSES (Gasket x Gasket x Gasket x Gasket)

C900 (DR18)

4, 6, 8, 10, 12

C905 (DR18)

14, 16, 18, 20, 24

C905 (DR25)

30, 36

BENDS 1° to 90° (Gasket x Gasket or Gasket x Spigot)

C900 (DR18)
4, 6, 8, 10, 12

C905 (DR18)
14, 16, 18, 20, 24

C905 (DR25)
30, 36

INCREASER (Gasket x Gasket or Gasket x Spigot)

C900 (DR18 or DR25)
4 X 6, 8, 10, 12, 14, 16, 18, 20, 24, 30, 36
6 X 8, 10, 12, 14, 16, 18, 20, 24, 30, 36
8 X 10, 12, 14, 16, 18, 20, 24, 30, 36
10 X 12, 14, 16, 18, 20, 24, 30, 36
12 X 14, 16, 18, 20, 24, 30, 36
14 X 16, 18, 20, 24, 30, 36
16 X 18, 20, 24, 30, 36
18 X 20, 24, 30, 36
20 X 24, 30, 36

C905 (DR18 or DR25)
24 X 30, 36
30 X 36

STOP COUPLINGS

C900 (DR18)
4, 6, 8, 10, 12

C905 (DR18)
14, 16, 18, 20, 24

C905 (DR25)
30, 36

REPAIR COUPLINGS

C900 (DR18)
4, 6, 8, 10, 12

C905 (DR18)
14, 16, 18, 20, 24

C905 (DR25)
30, 36

CAPS (Gasket)

C900 (DR18)
4, 6, 8, 10, 12

C905 (DR18)
14, 16, 18, 20, 24

C905 (DR25)
30, 36

5° L SWEEP BEND (Gasket x Spigot)

C900 (DR18)
4, 6, 8, 10, 12, 14, 16, 18, 20, 24

C900 (DR25)
30, 36

SPIGOT PLUG

C900
4, 6, 8, 10, 12, 14, 16, 18, 20, 24, 30, 36

Attribute	Value
Criteria	CSA B137.0 (2005)
Criteria	CSA B137.3 (2005)
CSI Code	22 40 00 Plumbing Fixtures
Intertek Services	Certification
Listed or Inspected	LISTED
Listing Section	PLUMBING FITTINGS & ACCESSORIES
Report Number	3151399COQ-004
Spec ID	17954